

PROJECT: \_\_\_\_\_ ITEM NO: \_\_\_\_\_ QUANTITY: \_\_\_\_\_



**SERIES D-6" ROTOR**

3/4 HP   
  1 HP   
  1.5 HP   
  2 HP

**SPECIFICATIONS**

**APPLICATION:** Salad prep areas and areas of small volume and light waste.

**SPECIFICATIONS:** Disposer to be a Master Disposer Model D(HP) - (Chamber Style) - (Mounting Assm.) - (Control & Voltage)  
 6" Diameter Rotor/Turntable with 2 integral impact breakers constructed of hardened ductile steel alloy for long life use. Matching Sizing Ring with 20 grind teeth constructed of hardened ductile steel alloy. 4 3/4" throat opening. Low body chamber with force feed directional deflectors. Bolt on grind chamber for ease of removing disposer during servicing. Cast in discharge flange. Water inlet in waste chamber wall. Bolt on "Continuous Duty" motor for easy removal. Exclusive shaft extension with 1/2" wrench flats to externally de-jam foreign matter without special tools. Heavy cast alloy construction providing an extra long life disposer.

**MOUNTING ASSEMBLIES:**

- "SK" 4 3/4" Sink Adaptor  
INCLUDES: Vacuum Breaker, Flow Control, Stopper or Silver Saver
- "SK" 8 1/4" Sink/Trough Adaptor  
INCLUDES: Vacuum Breaker, Flow Control, and Silver Saver
- "BC" 12" or 18" Bowl Cone  
INCLUDES: Vacuum Breaker, Flow Control, and Silver Saver

"L" LOW CHAMBER (STANDARD)



**ADAPTORS:** Available for replacing any make disposer with a MASTER

**CONTROL GROUP:** (Includes Solenoid)



"MAN"  
Manual Starter



"MAN REV"  
Manual Reversing Starter

**AUTOMATIC REVERSING PREFABRICATED CONTROL CENTERS:**



"CR"  
• Auto Rev



"CRTW"  
• Auto Rev  
• Timed Water  
• Afterrun



"CCRM"  
• Auto Rev  
• Timed Water and  
• Motor Afterrun

(For further information see "Controls Specification Sheet" other controls available, consult factory)

**EXAMPLE OF DATA SEQUENCE FOR SPECIFICATION AND ORDERING**



